
NASA TECH BRIEF



NASA Tech Briefs are issued by the Technology Utilization Division to summarize specific technical innovations derived from the space program. Copies are available to the public from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia, 22151.

Oscillator Circuit Measures Liquid Level in Tanks



The problem: Accurately measuring the level of a liquid in a tank by electronic means. The measurement system must operate automatically without moving parts and provide an output signal of liquid level that can be transmitted to a remote recorder.

The solution: An oscillator circuit employing a twin transmission line as a liquid level probe.

How it's done: A continuous loop of twin transmission line extending through the liquid in the tank is connected to a transistorized 5-mc oscillator. The

oscillation frequency of this resonant circuit for a liquid of given dielectric constant is directly proportional to the level (depth) of liquid in the tank. Since the system losses are only a few db in this relatively low-frequency system, the oscillation frequency is almost totally determined by line length rather than transistor characteristics, resulting in excellent frequency stability. A conventional 10-mc digital counter connected to the oscillator circuit is used to provide a readout of the oscillation frequency, which in turn is a direct measure of the liquid level.

This document was prepared under the sponsorship of the National Aeronautics and Space-Administration. Neither the United States Government, nor NASA, nor any person acting on behalf of NASA: A. Makes any warranty or representation, express or implied, with respect to the accuracy, completeness, or usefulness of the information contained in

this document, or that the use of any information, apparatus, method, or process disclosed in this document may not infringe privately-owned rights; or B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of, any information, apparatus, method, or process disclosed in this document.

Notes:

- 1. The separation between the two legs of the loop must be at least ten times the spacing between the twin conductors comprising the line in order to minimize coupling effects.
- 2. Instead of using a continuous loop of twin transmission line, one leg of line terminated in an open circuit at the bottom of the tank may be used. This arrangement, however, may produce large errors because of signal reflections from the surface of the liquid and the tank bottom.
- 3. Inquiries concerning this invention may be directed to:

Technology Utilization Officer Marshall Space Flight Center Huntsville, Alabama, 35812 Reference: B65-10209

Patent status: NASA encourages the immediate use of this invention. Inquiries about obtaining rights for its commercial use may be made to NASA, Code AGP, Washington, D.C., 20546.

Source: International Business Machines under contract to Marshall Space Flight Center (M-FS-245)